BIRD v2 update

New features, in-progress features, and one dirty trick

Maria Jan Matejka • jan.matejka@nic.cz • 23 May 2019



Custom route attributes

- New feature since v2.0.4
- attribute int is_blackhole;
 ...
 filter { ...
 if (myas, 666) ~ bgp_ext_community then
 is_blackhole = 1;
 else
 is_blackhole = 0;
- Types: int, IP addr, community list, BGP path



Filter benchmark tool: protocol perf

- Run random routes through the given filter
- Collect data from log

```
2019-05-21 16:57:48.913 <INFO>
Perf v2.0.4-57-g96d757c1 perf_none
exp=16 times:
gen=4320081 temp=1939327
update=2936133 withdraw=1620441
```

• Date, time, version, protocol instance name, $2^{16} = 65536$ routes, 2.9 ms update time



Import table

- Store routes before import filter is run
- Filter reload without route refresh
- Eats some memory to store the routes
- Compatible with import keep filtered;
- Configure as import table on; in channel config



Route autoreload on RPKI change

- Is NOT MERGED YET
- Dirty workaround
 - Set debug { routes }; in RPKI protocol config
 - Parse log by script and detect ROA changes
 - Invoke reload in in CLI for every affected protocol
- To be released in several months, hopefully
- Import table will be required to do autoreload



Faster filters

- Not finished yet
- New (and faster!) filter interpretter
- Thread safe execution
- Type check in configure time
- Better data model



You can upgrade now

BIRD 2 is the new BIRD

Maria Jan Matejka • jan.matejka@nic.cz

